

2017 Buick Truck Encore FWD L4-1.4L Turbo VIN B

Vehicle &gt; Maintenance &gt; Fluids &gt; Fluid - A/T &gt; Specifications

## FLUID TYPES AND CAPACITIES

## Fluid Types and Capacities

## Fluid and Lubricant Recommendations

Document ID: 4353356

Usage	Fluid/Lubricant
Engine Oil	Use only engine oil licensed to the dexos™ 1 specification, or equivalent, of the proper SAE viscosity grade. ACDelco dexos™ 1 Synthetic Blend is recommended. Use SAE 5W-30 viscosity grade engine oil.  Cold Temperature Operation: In an area of extreme cold, where the temperature falls below -29 °C (-20 °F), an SAE 0W-30 oil may be used. An oil of this viscosity grade will provide easier cold starting for the engine at extremely low temperatures. When selecting an oil of the appropriate viscosity grade, always select an oil of the correct specification. Refer to Owner's Manual for more information.
Engine Coolant	50/50 mixture of clean, drinkable water and use only DEX-COOL Coolant.
Hydraulic Brake/Clutch System (Vehicles with DOT 3 brake fluid)	DOT 3 Hydraulic Brake Fluid (GM Part No. 19299818, in Canada 19299819).
Hydraulic Brake/Clutch System (Vehicles with DOT 4 brake fluid)	DOT 4 Hydraulic Brake Fluid (GM Part No. 19299570, in Canada 19299571).
Windshield Washer	Automotive windshield washer fluid that meets regional freeze protection requirements.
Automatic Transmission	DEXRON®-VI Automatic Transmission Fluid
Manual Transmission	Manual Transmission Fluid (GM Part No. 19259104, in Canada 19259105).
Transfer Case (All-Wheel Drive)	Transfer Case Fluid (GM Part No. 19256084, in Canada 19256085).
Key Lock Cylinders	Multi-Purpose Lubricant, Superlube (GM Part No. 12346241, in Canada 10953474).

Usage	Fluid/Lubricant
Hood Latch Assembly, Secondary Latch, Pivots, Spring Anchor, and Release Pawl	Lubriplate Lubricant Aerosol (GM Part No. 89021668, in Canada 89021674) or lubricant meeting requirements of NLGI #2, Category LB or GC-LB.
Hood and Door Hinges	Multi-Purpose Lubricant, Superlube (GM Part No. 12346241, in Canada 10953474).
Weatherstrip Conditioning	Weatherstrip Lubricant (GM Part No. 3634770, in Canada 10953518) or Dielectric Silicone Grease (GM Part No. 12345579, in Canada 10953481).
Rear Axle Fluid	DEXRON® Gear Oil 75W-90 (GM Part No 9986285).

Fluids, Lubricants, and Sealers">

### 6T40 (MNH MNK) - Automatic Transmission -> Adhesives, Fluids, Lubricants, and Sealers

Document ID: 2330174

Application	Type of Material	GM Part Number	
		United States	Canada
Automatic Transmission Fluid	DEXRON®VI	88861037	19264717
Torque Converter Bolts	Threadlock	12345382	10953489

### 6T40 (MNH MNK) - Automatic Transmission -> Approximate Fluid Capacities

Document ID: 1905750

Application	Specification	
	Metric	English
6T40/6T45/6T50		
• Valve Body Cover Removal – Approximate Capacity	5.0–7.0 liters	5.3–7.4 quarts
• Fluid Change – Drain Plug – Approximate Capacity	4.0–6.0 liters	4.2– 6.3 quarts
• Overhaul – Approximate Capacity	8.0–8.5 liters	8.5–9.0 quarts

